Arm SystemReady Requirements Specification v1.1

arm SystemReady

Copyright © 2020, 2021 Arm Limited or its affiliates. All rights reserved. Document number: DEN0109B

Arm SystemReady Requirements Specification

Copyright © 2020, 2021 Arm Limited or its affiliates. All rights reserved.

Release information

The Change History table lists the changes made to this document.

Date	Issue	Confidentiality	Change		
6 Oct 2020	А	Non-Confidential	Arm SystemReady Requirements Specification version 1.0		
27 April 2021	В	Non-Confidential	Arm SystemReady Requirements Specification version 1.1		
			 Updated requirements for SystemReady SR v2.0, ES v1.0 and IR v1.0 		
			 Reformatted the guidance for possible requirements for future versions 		
			 Renamed "security option" to "security extension" 		
			 Removed the Pre-silicon Certification as Pre-silicon is an enabler and tool not a requirement or certification program 		
			 Added waiver levels for SystemReady ES and IR 		
			Added certification process flow chart		

Table 1-1 Change History

Contents

1	INTR	ODUCTI	ON	6		
2	ARM SYSTEMREADY PROGRAM					
	2.1	System	Ready SR certification	7		
		2.1.1	SystemReady SR V2.0 requirements, April 2021 update	7		
		2.1.2	Future SystemReady SR requirements	7		
	2.2	System	Ready ES certification	7		
		2.2.1	SystemReady ES V1.0 requirements, April 2021 update	7		
		2.2.2	Future SystemReady ES requirements	8		
	2.3	Ready IR certification	8			
		2.3.1	SystemReady IR V1.0 requirements, June 2021	8		
		2.3.2	Future SystemReady IR requirements	8		
	2.4	System	Ready LS certification, under development	8		
3	SYS	FEMREA	DY OPT-IN EXTENSIONS	8		
	3.1	Security	/ Extension	8		
		3.1.1	SystemReady Security Extension requirements, under development	8		
APPI	ENDIX	Α	SYSTEMREADY ES AND IR WAIVER LEVELS	9		
APPI	ENDIX	В	SYSTEMREADY CERTIFICATION PROCESS	12		

Arm Non-Confidential Document Licence ("Licence")

This Licence is a legal agreement between you and Arm Limited ("**Arm**") for the use of Arm's intellectual property (including, without limitation, any copyright) embodied in the document accompanying this Licence ("**Document**"). Arm licenses its intellectual property in the Document to you on condition that you agree to the terms of this Licence. By using or copying the Document you indicate that you agree to be bound by the terms of this Licence.

"Subsidiary" means any company the majority of whose voting shares is now or hereafter owner or controlled, directly or indirectly, by you. A company shall be a Subsidiary only for the period during which such control exists.

This Document is **NON-CONFIDENTIAL** and any use by you and your Subsidiaries ("Licensee") is subject to the terms of this Licence between you and Arm.

Subject to the terms and conditions of this Licence, Arm hereby grants to Licensee under the intellectual property in the Document owned or controlled by Arm, a non-exclusive, non-transferable, non-sub-licensable, royalty-free, worldwide licence to:

- (i) use and copy the Document for the purpose of designing and having designed products that comply with the Document;
- (ii) manufacture and have manufactured products which have been created under the licence granted in (i) above; and
- (iii) sell, supply and distribute products which have been created under the licence granted in (i) above.

Licensee hereby agrees that the licences granted above shall not extend to any portion or function of a product that is not itself compliant with part of the Document.

Except as expressly licensed above, Licensee acquires no right, title or interest in any Arm technology or any intellectual property embodied therein.

THE DOCUMENT IS PROVIDED "AS IS". ARM PROVIDES NO REPRESENTATIONS AND NO WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY, SATISFACTORY QUALITY, NON-INFRINGEMENT OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE DOCUMENT. Arm may make changes to the Document at any time and without notice. For the avoidance of doubt, Arm makes no representation with respect to, and has undertaken no analysis to identify or understand the scope and content of, third party patents, copyrights, trade secrets, or other rights.

NOTWITHSTANING ANYTHING TO THE CONTRARY CONTAINED IN THIS LICENCE, TO THE FULLEST EXTENT PETMITTED BY LAW, IN NO EVENT WILL ARM BE LIABLE FOR ANY DAMAGES, IN CONTRACT, TORT OR OTHERWISE, IN CONNECTION WITH THE SUBJECT MATTER OF THIS LICENCE (INCLUDING WITHOUT LIMITATION) (I) LICENSEE'S USE OF THE DOCUMENT; AND (II) THE IMPLEMENTATION OF THE DOCUMENT IN ANY PRODUCT CREATED BY LICENSEE UNDER THIS LICENCE). THE EXISTENCE OF MORE THAN ONE CLAIM OR SUIT WILL NOT ENLARGE OR EXTEND THE LIMIT. LICENSEE RELEASES ARM FROM ALL OBLIGATIONS, LIABILITY, CLAIMS OR DEMANDS IN EXCESS OF THIS LIMITATION.

This Licence shall remain in force until terminated by Licensee or by Arm. Without prejudice to any of its other rights, if Licensee is in breach of any of the terms and conditions of this Licence then Arm may terminate this Licence immediately upon giving written notice to Licensee. Licensee may terminate this Licence at any time. Upon termination of this Licence by Licensee or by

Arm, Licensee shall stop using the Document and destroy all copies of the Document in its possession. Upon termination of this Licence, all terms shall survive except for the licence grants.

Any breach of this Licence by a Subsidiary shall entitle Arm to terminate this Licence as if you were the party in breach. Any termination of this Licence shall be effective in respect of all Subsidiaries. Any rights granted to any Subsidiary hereunder shall automatically terminate upon such Subsidiary ceasing to be a Subsidiary.

The Document consists solely of commercial items. Licensee shall be responsible for ensuring that any use, duplication or disclosure of the Document complies fully with any relevant export laws and regulations to assure that the Document or any portion thereof is not exported, directly or indirectly, in violation of such export laws.

This Licence may be translated into other languages for convenience, and Licensee agrees that if there is any conflict between the English version of this Licence and any translation, the terms of the English version of this Licence shall prevail.

The Arm corporate logo and words marked with ® or [™] are registered trademarks or trademarks of Arm Limited (or its subsidiaries) in the US and/or elsewhere. All rights reserved. Other brands and names mentioned in this document may be the trademarks of their respective owners. No licence, express, implied or otherwise, is granted to Licensee under this Licence, to use the Arm trade marks in connection with the Document or any products based thereon. Visit Arm's website at <u>https://www.arm.com/company/policies/trademarks</u> for more information about Arm's trademarks.

The validity, construction and performance of this Licence shall be governed by English Law.

Copyright © [2020, 2021] Arm Limited (or its affiliates). All rights reserved.

Arm Limited. Company 02557590 registered in England. 110 Fulbourn Road, Cambridge, England CB1 9NJ.

Arm document reference: LES-PRE-21585 version 4.0

1 INTRODUCTION

Systems that are designed to "just work" for the end user (with the ability to install and run generic off-the-shelf operating systems out-of-the-box) need to follow a set of minimum hardware and firmware requirements to ensure compatibility.

For hardware, the Arm SystemReady Program defines a common <u>Base System Architecture</u> (BSA) specification and a set of market specific supplements. For example, the Server Base System Architecture (SBSA) supplement specification is for the server segment. The common BSA contains only the bare minimum requirement to deploy an operating system. The BSA is a baseline. Therefore, there is no limit on differentiation and the special features that can be built atop the base platform. The platform can be adapted to meet the market need.

For firmware, the program has added additional boot recipes – a recipe meaning a set of requirements - to accommodate the different standards and implementations that are used in a broader ecosystem. The recipes SBBR, EBBR and LBBR are described in the <u>Base Boot Requirements</u> (BBR) specification. Arm may develop other recipes in the future, if necessary.

This specification describes the requirements for Arm SystemReady program.

2 ARM SYSTEMREADY PROGRAM

For the Arm SystemReady program, each market segment may target a different set of operating systems and hypervisors with different hardware and firmware requirements. We use the term band is used to identify these differences with an abbreviation for each band:

- SR for ServerReady
- LS for LinuxBoot Server
- ES for Embedded Server
- IR for IoT

Table 1 summarizes the specifications that the devices need to be compliant with.

Certification	Specifications			
SystemReady SR	BSA	SBSA	SBBR Recipe in BBR	
SystemReady LS	BSA	SBSA	LBBR Recipe in BBR	
SystemReady ES	BSA	-	SBBR Recipe in BBR	
SystemReady IR	BSA	-	EBBR Recipe in BBR and devicetree	

Table 1: Arm SystemReady bands

SystemReady SR is technically identical to ServerReady and continues to bring the same benefits to the Arm server ecosystem. The additional bands in SystemReady, LS, ES, and IR, are designed to serve the needs of a broader silicon and software ecosystem. We define the bands in consultation with our partners, and we expect that all operating system distributions will find a band that adequately captures their basic requirements for a standards-based Arm platform.

All SystemReady bands will be supported by a common Architectural Compliance Suite (ACS) that is modular, to support testing against different combinations of specifications required by a SystemReady band.

SystemReady ES, and IR for 64-bit, have the same hardware requirements.

- SystemReady IR requires <u>devicetree</u> support in addition to the reduced set of UEFI interfaces that are specified in the <u>EBBR specification</u>.
- SystemReady ES requires ACPI and SMBIOS interfaces, in addition to the UEFI interfaces.

SystemReady SR requires additional SBSA compliance for hardware and more stringent UEFI and ACPI requirements for firmware.

Systems that are certified as SystemReady SR meet the requirements for SystemReady ES. There is no need for these systems to be certified as SystemReady ES.

A 32-bit system can be certified as SystemReady IR if it supports devicetree and the EBBR specification. However, because the BSA specification does not cover 32-bit systems, we list the 32-bit systems separately from the 64-bit systems on the Arm SystemReady System Compatibility List (SCL).

2.1 SystemReady SR certification

2.1.1 SystemReady SR V2.0 requirements, April 2021 update

SystemReady SR v2.0 requires the certified devices to be compliant to the following specifications:

- BSA v1.0 and Level 3-6 as defined in SBSA Supplement v6.1
- SBBR recipe in BBR v1.0

To certify a device for SystemReady SR v2.0, results from the running the existing <u>Enterprise ACR v3.0</u> must be submitted. In addition, OS installation logs are needed:

- WinPE installation log is required
- VMware ESXi-Arm installation log is recommended
- Installation logs from two of the Linux or BSD distros are required

In choosing the Linux or BSD distros, maximize the coverage by diversifying the heritage and page size. For example, the following shows the grouping of the heritage and the page size:

- Heritage: RHEL/Fedora/CentOS, or SLES/openSUSE, or Ubuntu/Debian, or CBL-Mariner, or NetBSD/OpenBSD/FreeBSD
- Page size: for example, RHEL/CentOS are 64K, and Ubuntu/Fedora are 4K

2.1.2 Future SystemReady SR requirements

In the future, requirements based on newer versions of the BSA/SBSA/BBR specifications may be added. In addition, installation log from VMware ESXi-Arm may be required.

2.2 SystemReady ES certification

2.2.1 SystemReady ES V1.0 requirements, April 2021 update

SystemReady ES v1.0 requires the certified devices to be compliant to the following specifications:

- BSA v1.0
- SBBR recipe in BBR v1.0

Waiver Levels 0-2 as defined in Appendix A are available.

To certify a device for SystemReady ES v1.0, results from the running the existing <u>Enterprise ACR v3.0</u> must be submitted. In addition, OS installation logs are needed:

- WinPE installation log is recommended
- VMware ESXi-Arm installation log is recommended
- Installation logs from two of the Linux or BSD distros are required

In choosing the Linux or BSD distros, maximize the coverage by diversifying the heritage and page size. For example, the following shows the grouping of the heritage and the page size:

- Heritage: RHEL/Fedora/CentOS, or SLES/openSUSE, or Ubuntu/Debian, or CBL-Mariner, or NetBSD/OpenBSD/FreeBSD
- Page size: for example, RHEL/CentOS are 64K, and Ubuntu/Fedora are 4K

2.2.2 Future SystemReady ES requirements

In the future, requirements based on newer versions of the BSA/BBR specifications may be added. In addition, installation logs from WinPE and VMware ESXi-Arm may be required. Waiver Levels 0-1 may be deprecated.

2.3 SystemReady IR certification

2.3.1 SystemReady IR V1.0 requirements, June 2021

SystemReady IR v1.0 requires the certified devices to be compliant to the following specifications:

- BSA v1.0 for 64-bit devices, no BSA requirements for 32-bit devices
- EBBR recipe in BBR v1.0 (Note: EBBR recipe is based on the EBBR Specification 2.0.0. This will be updated in the next revision of the BBR specification)
- devicetree v0.3

Waiver Levels 0-2 as defined in Appendix A are available.

To certify a device for SystemReady IR v1.0, results from the running the ACS-IR v1.0 must be submitted. In addition, installation logs from two of the Linux or BSD distros are required. The recommended distros are Fedora, Debian, Ubuntu, openSUSE and CBL-Mariner.

2.3.2 Future SystemReady IR requirements

In the future, requirements based on newer versions of the BSA/BBR specifications may be added. Waiver Levels 0-1 may be deprecated.

2.4 SystemReady LS certification, under development

The SystemReady LS requirements and the ACS-LS are under development.

3 SYSTEMREADY OPT-IN EXTENSIONS

3.1 Security Extension

The Arm SystemReady Program provides a Security Extension for devices that are compliant to the UEFI Secure Boot and Secure Firmware Update through Capsule Update services. The requirements are specified in the Base Boot Security Requirements (BBSR) specification.

3.1.1 SystemReady Security Extension requirements, under development

SystemReady Security Extension requires the certified devices to be compliant to the BBSR Specification.

To certify a device for SystemReady Security Extension, results from the running the ACS Security Extension v1.0 must be submitted. ACS for Security Extension is underdevelopment.

APPENDIX A SYSTEMREADY ES AND IR WAIVER LEVELS

Currently, most of the Arm SoCs targeting the embedded server and IoT markets are not BSA compliant. For existing SoCs targeting the embedded server and IoT markets, there are three possibilities for SystemReady ES and IR certification:

- Level 2 Waiver: Like with any certification programs, some failures are expected. Waivers are granted, as long as the user experience of software "just works" is not impacted.
- Level 1 Waiver and Workaround: Major failures may exist. However, the user experience of software "just works" can still be mostly achieved using hardware or firmware workarounds. Significant investments may be needed to provide the workaround.
- Level 0 Waiver and OS Change: Major failures may exist, and hardware or firmware workarounds are not sufficient. OS changes or workarounds are needed. The user experience of software "just works" is impacted until the OS changes are contained in the future OS releases.

Level 0 waivers put the system at risk of compromising the SystemReady vision of software "just works". However, it is still important at this stage to fully understand the existing SoCs in their journey to be fully BSA compliant in the next generation. Devices with this class of failures can be certified at Level 0, if the required OS change or fix is available and meets the following requirements:

Linux / BSD

- Fix is up-streamed. For example, Linux kernel.org, or linux-next, or equivalent for BSDs.
- Fix is available and tested in a public distro build like:
 - Alpha / beta /development distro release
 - Nightly build, for example Fedora Rawhide, OpenSUSE Tumbleweed, Ubuntu Daily Build, <u>Arch Linux</u> kernel build

Windows and VMware ESXi, for SystemReady ES

- Fix applied by a driver, for example OSV, OEM, or community, that can be injected in the OS image during deployment or installation. Driver could be available as open-source or public binary.
- Fix confirmed by OSV and is available and tested in a public beta or pre-release build, for example Windows Insider Preview or VMware Fling

Table 2 describes some of the details of the SystemReady ES and IR waiver levels. These levels do not apply to SystemReady SR or LS:

Criteria	Level 0 – Waiver + OS Change	Level 1 – Waiver + Workaround	Level 2 – Waiver
Hardware BSA compliant?	No. Major failures, resolved with OS change	No. Major failures, resolved with workarounds	Mostly yes, some failures
Firmware BBR compliant?	Mostly yes. Some or no failures	Mostly yes. Some or no failures	Mostly yes. Some or no failures
Hardware or Firmware workarounds?	Not possible, or inadequate solution. An OS change is required instead.	Required, provide good solution	Not needed
Impacts "just works" goal?	Yes. Must be resolved with an OS change	With workaround, no impacts	No
Impacts user experience?	Yes. Must be contained with an OS change	With workaround, impacts are minimal or contained (with workaround)	Minimal or contained
OS changes needed?	Yes, required to enable "just works" goal and resolve user experience issues. Based on upstream or public OS builds.	Optional. OS changes can be used, for example, to remove the need for the workaround, add missing drivers or SoC support.	No
Existing OS distros work?	No, or less than two	Yes, two or more work with workaround	Yes, two or more, typically more
Future OS distros work?	Yes, some, two or more work with OS changes	Yes, most work with or without workaround	Yes, most
Future Hardware resolves issue?	Possible, not required. Partner committed to BSA	Possible, not required. Partner committed to BSA	Possible, not required. Partner committed to BSA
Waiver type	Public waiver issued to partner. Partner may request confidential waiver instead for ES band. Public errata describing issues and future path published on Arm SystemReady Certification List.	Public waiver issued to partner. Partner may request confidential waiver instead for ES band. Partner documentation of workarounds, public or NDA to end customers, are needed.	Confidential waiver issued to partner. No public documentation needed.

Table 2: SystemReady ES and IR waiver levels

Figure 1 shows a simplified summary of the SystemReady ES and IR waiver levels.



Figure 1: Summary of SystemReady ES and IR waiver levels

Time limit

The use of these levels will be time limited, with a requirement that any new certification submissions after these dates must be certified at a higher Level. The exact cutoff dates for Level 0 and Level 1 are to be determined.

APPENDIX B SYSTEMREADY CERTIFICATION PROCESS

The following flow chart illustrates the Arm SystemReady certification process from the initial certification request to the completion of the certification. This chart identifies the tasks and responsibilities that Arm and partners have throughout the process. Arm may use third party engineering services and test labs to strategically enable firmware development with partners, or to assist in the final certification phase. Arm is responsible for the architect final review and approval, as well as the final certificate issurance and publication.

